

Manufacturer's Declaration

We, SWISS KRONO TEX GmbH & Co. KG, grant an additional warranty covering the wear resistance of SUPERIOR laminate floors in accordance with the provisions below. The warranty period depends on the type of utilization (private or commercial) and begins with the date of purchase.

Collection	private	commercial
Advanced plus	25 years	3 years
Advanced	25 years	3 years
Catwalk	25 years	3 years
Standard plus	20 years	2 years
Standard	20 years	2 years
Basic	6 years	-

Warranty Conditions

SUPERIOR laminate floor panels must be checked for defects prior to and during their installation. Any SUPERIOR laminate flooring installed despite exhibiting visible defects is excluded from the warranty. SUPERIOR laminate flooring of the appropriate wear-resistance class must be properly installed in dry rooms in accordance with the installation instructions.

Any SUPERIOR laminate flooring installed in moist rooms is excluded from the warranty. Cases of wear on SUPERIOR laminate flooring must be visible over an area of at least one square centimeter, and in particular the décor layer must be completely worn away. Wear at the edges of elements and any damage caused by abnormal and inappropriate wear, and especially by mechanical action, are excluded from the warranty. The warranty is voided unless the SUPERIOR laminate flooring is regularly cleaned and cared for. Any warranty claims must be submitted together with the original invoice to the merchant who made the sale within 30 days of discovering the wear. SWISS KRONO TEX GmbH & Co. KG reserves the right to inspect affected floors on-site to determine whether warranty claims are justified.

Warranty Fulfilment

In cases covered by the warranty, SWISS KRONO TEX GmbH & Co. KG will replace the damaged elements. If the affected SUPERIOR laminate flooring is no longer available, the buyer may select another flooring of equivalent quality from the current SUPERIOR range. As it may be assumed that SUPERIOR laminate flooring depreciates at the rate of ten percent yearly as a result of normal wear and tear, SWISS KRONO TEX GmbH & Co. KG will charge the customer the accumulated amount of the depreciation as a condition for supplying the replacement. No liability is accepted for any other damages, and in particular not for ancillary damages such as costs incurred for the removal and transport of damaged SUPERIOR flooring or the installation of new flooring.

Heiligengrabe, Germany, April 9th 2020



Thomas Schmaltz, Head of Quality Assurance

Standard Plus

Kurzbeschreibung:	Laminatboden
Abmessungen:	1380 x 193 x 7 mm
Anwendungsbereiche:	Zur Verwendung im trockenen Innenbereich – privat, sowie im Trockenbereich - gewerblich
Garantie:	20 Jahre privat / 2 Jahre gewerblich gemäß KRONOTEX Garantiebedingungen
Produktaufbau:	Laminatboden der Nutzungsklasse 32 / AC 4 Aus widerstandsfähigem / hochabriebfestem Overlay, Dekorpapier, quellungsarmer HDF-Trägerplatte und Gegenzugpapier. Leimfreies Clic-Verlegesystem
	Beständigkeit gegen Abrieb und Stoßbeanspruchung gemäß Norm DIN EN 15468
	Formaldehydgehalt (EN 717-1) < 0,05 ppm
	Fleckenunempfindlichkeit (EN 438) Grad 5, keine sichtbaren Veränderungen der Oberfläche
	Lichtechtheit (EN ISO 105-B02 / EN 20 105-A02) Blauwollskala, nicht schlechter als 6 Graumaßstab, nicht schlechter als 4
	Brandverhalten (EN 13501-1) schwer entflammbar, mindestens C _{fl} -s1
	Wärmedurchlasswiderstand (DIN EN 12667) 0,056 m ² K/W

Hinweise:

Verlegung nur gemäß Herstellerangaben.

Alle produktspezifischen Angaben sind Richtwerte - produktionsbedingte Schwankungen sind nicht auszuschließen. Technische Änderungen vorbehalten.

Stand: Mai 2020



Wood at its best



GERMANY



Certificate

EN

SUPERIOR STANDARD PLUS

USE CLASS	31 (DIN EN ISO 10874)
ABRASION CLASS	AC 3
DIMENSIONS	1380 × 193 × 7 mm
EXAMPLE OF APPLICATION	Small office
GUARANTEE	20 years in living area 2 years in commercial area

according to SUPERIOR guarantee

The right to technical modifications is reserved.


Uwe Jöst
Managing Director




Robert Schneider
Sales Direktor



www.blauer-engel.de/176



EN 14041



Made in Germany